

# TECHNICAL DATA SHEET

## Diesel particulate filter cleaner

**Art. no. 5861 014 500**

P. Qty.: 1 / 12

### Cleaner for removing carbon and ash deposits from diesel particulate filters

Contents	400 ml
Colour	Rosy
Smell/fragrance	Aminic
Chemical basis	Water
Shelf life from production	15 Month
Density	1.01 g/cm <sup>3</sup>
Density conditions	at 20° C
pH value	11.47



### Application area

- Remove the temperature or pressure sensor
- Insert the probe into the hole created and spray in the direction of the particulate filter to empty
- Recovery then needs to be initiated manually via the tester or by taking a test drive
- Interrogate the fault memory following recovery and delete any errors if necessary. One can is sufficient for one particulate filter

### Notice

This information is intended to advise you, to the best of our knowledge, based on our tests and experience. Preliminary testing required! For more information, please refer to the technical data sheet.

The usage instructions are recommendations based on the tests we have conducted and based on our experience; carry out your own tests before each application. Due to the large number of applications and storage and processing conditions, we do not assume any liability for a specific application result. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.